

Open emacs without window	emacs -nw	----	(s) Previous Cmd	M-p
Quit	C-x C-c		(s) Next Cmd	M-n
Describe mode	C-h m		(s) Compile and Execute buffer	C-c C-k
Menu bar	Escape ~		(s) Compile current line	C-c C-c
Find file	C-x C-f		Incremental Search	C-s
Save file	C-x C-s		Search Backwards	C-r
Help	C-h C-t		Search for Marked Text	C-s M-y
Save file as	C-x C-w		Simple Replace	M-% (y,n,! *all*)
Undo	C-_		Regular Expression Replace	C-M-% (C-u C-SP)
Begin of line	C-a		Search for TAG	M-.
End of line	C-e		Bookmark Set	C-x rm
End of file	M-<>		Jump to bookmark	C-x rb
Close buffer	C-x k		List bookmarks	M-x list-bookmarks
Switch between buffers on screen	C-x o		Spell Check	M-x flyspell-mode
Maximize current buffer	C-x 1		Spell Check word on point	M-\$
Split current buffer	C-x 2		Major Mode Keybindings	C-h m
Switch to different buffer	C-x b			
List all buffers	C-x C-b			
Kill line (cut from point to end)	C-k			
Mark region	C-space			
Cut from here to mark	C-w			
Copy from here to mark	M-w			
Paste	C-y			
Escape (mini buffer)	C-g			
Go to line	M-g			
Revert to last save	M-x revert-buffer			
Create new frame	C-x 52			
Give frame focus	C-x 5o			
Close frame	C-x 50			

- .emacs file *Do not create this file instead, create the init.el file in the **.emacs.d** directory*
- *** File has changed %%* Read only
- Seeing the content of Message buffer
C-x b
type ***Messages***
to exit C-x b
- *Buffers that do not correspond to a file on a disk have * in their name.*
- *Often used commands are like C-letter, less often C-x C-xxx*
- *Mode commands C-c*
- *Kill ring refers to the clipboard*
- *Can remotely edit files over scp*
- (global-set-key [(meta g)] 'goto-line) for setup **go to line**
- Managing windows
 - C-x C-b
 - In the list, press 1 to switch to that file, d to mark for deletion, s for save and x for execute.
- To start **mark** C-Space, then either C-w for **Cut** or M-w for **Copy**
- C-s for **search**, C-s **again** to search for next occurrence.
- When searching, if you want **case sensitive** input the string in the same case.
- When doing search and replace, if match is all upper replacement is also converted to upper.
- To see only lines of occurrence, type M-x occur <str> then switch to buffer *OCCUR*
- **etags** *.java, creates index files for all the *.java files in a directory. For clojure 'etags -l lisp *.clj'
- *Check value of load-path* using C-h v load-path RET
- Emacs grep <http://www.emacswiki.org/emacs/GrepMode>
- Emacs **manual** http://www.gnu.org/software/emacs/manual/html_node/emacs/index.html from within **emacs C-h i (info) d (root) m (open) emacs**
- Good article about learning Emacs <http://edward.oconnor.cx/2009/07/learn-emacs-in-ten-years>
- TODO Email, Spell Check, RSS
- **Emacs+Cloure :**
 - Include :dev-dependencies [[leiningen/lein-swank "1.1.0"]] in project.clj
 - run lein swank
 - in emacs type M-x slime-connect (Uses port 4005)